


100V 20A Ultra Low VF Schottky

Characteristics Summary

Characteristics	Values	Units
IF(AV)	10 X 2	A
VRRM	100	V
VF @ 5A, TJ = 125°C	0.45	V, typ.
TJ Operating Junction Temperature	-40 to +150	°C



Features

- Ultra Low Forward Voltage (VF) Drop
- Very Low Reverse Leakage in high temperature.
- Softest, fast switching capability
- 150°C Operating Junction Temperature
- Lead Free Finish, RoHS Compliant

Typical Applications

Device optimized for low forward voltage drop to maximize efficiency in Power Supply applications.

- DC/DC Converters
- AC/DC Converters

Maximum Ratings Characteristics

(TA = 25°C unless otherwise specified)

Parameter	Symbol	Values	Units
DC Blocking Voltage	V _{RM}	100	V
Working Peak Reverse Voltage	V _{RWM}		V
Peak Repetitive Reverse Voltage	V _{RRM}		V
Average Rectified Forward Current Per device (Rated VR-20Khz Square Wave) – 50% duty cycle	I _D	10	A
Peak Forward Surge Current – 1/2 60hz	I _{FSM}	200	A
Peak Repetitive Reverse Surge Current (2uS-1Khz)	I _{RRM}	1	A
Typical Thermal Resistance (per leg) Package = TO-220F	R _{θJC}	4	°C / W
Isolation voltage (TO-220F only)	V _{AC}	1500	V
Maximum Rate of Voltage Change (at Rated VR)	dv/dt	10000	V/uS
Operating Junction Temperature	T _J	-40 to +150	°C
Storage Junction Temperature	T _{STG}	-40 to +150	

Electrical Characteristics – (per leg)

(TA = 25°C unless otherwise specified)

Parameter	Test Conditions		Symbol	Typ.	Max.	Units
Instantaneous Forward Voltage	IF = 5 A	TJ = 25°C	VF*	0.45	-----	V
	IF = 10 A			0.57	0.61	
	IF = 5 A	TJ = 125°C		0.40	-----	
	IF = 10 A			0.52	0.58	
Instantaneous Reverse Current	VR = 70V	TJ = 25°C	IR*	3.5	-----	uA
	VR = 100V			-----	40	uA
	VR = 70V	TJ = 125°C		4.0	-----	mA
	VR = 100V			7.0	25	mA
* Pulse width < 300 uS, Duty cycle < 2%						

* Pulse width < 300 uS, Duty cycle < 2%



Characteristics Curves

($T_A = 25^\circ\text{C}$ unless otherwise specified)




Figure 1 : Current Derating, Case




Figure 2 : Typical Junction Capacitance




Figure 3 : Typical Forward Voltage





Figure 4 : Typical Reverse Current

Ordering Information

Part No	Package	Packing	Finish	Halogen	Packing Unit
AD20D100F	TO-220F	Tube	Sn	Free	5,000ea

Marking Layout



LOGO IMAGE



1ST Line : Company logo

2nd Line : Date code


- WW : Work week calendar
- YY : Last one digit of calendar year

3rd Line : Device name

-F : TO-220F Full Molding PKG code

Package Dimensions

TO-220F



Revision History

No	Date	Contents
0	2016-10-17	Initial Brief Datasheet Release

<http://www.apsemi.com>

IMPORTANT NOTICE

AP Semiconductor co, Ltd reserves the right to make changes without further notice to any products or specifications herein. AP Semiconductor co, Ltd does not assume any responsibility for use of any its products for any particular purpose, nor does AP Semiconductor co, Ltd assume any liability arising out of the application or use of any its products or circuits. AP Semiconductor co, Ltd does not convey any license under its patent rights or other rights nor the rights of others.

AP Semiconductor Co., Ltd

Contact. Tel 82.70.4693.2299 FAX 82.70.4000.4009

E-mail: sales@apsemi.com

© 2015 AP semiconductor Co., Ltd. -Printed in KOREA -All Rights Reserved.

REV. 00