



Low Dropout Voltage Regulators

DESCRIPTION


The ISP278R05 is a low-dropout voltage regulator suitable for various electronic equipments. Dropout voltage of ISP278R05 Series is below 0.5V in full rated current (1.6A).

Cause the series have been designed for high current loads, so they are also used in lower current, extremely low dropout-critical systems (in which their tiny dropout voltage and ground current values are important attributes).

FEATURES

- $I_{OUT}=1.6A$; $V_{OUT}=5V$
- TO-220 Full Mold Package (4 pin)
- Internal over current protection, internal thermal shutdown
- Internal overvoltage protection, internal short-circuit protection
- Output disable function

Typical Application Circuit






Maximum Ratings


Characteristic	Symbol	Rating	Units
Input Voltage	V_i	18	V
Control Input Voltage	V_{CT}	18	V
Power Dissipation	Pd1(No Heat sink)	1.5	W
	Pd2(With Heat sink)	15	W
Junction Temperature	T_J	150	°C
Operating Temperature Range	T_{opr}	-20 ~ 80	°C
Storage Temperature Range	T_{stg}	-50 ~ 150	°C
Thermal shutdown Temperature	T_{tsd}	150	°C

Internal Block Diagram





Package Information



Package	Pin Info.
(TO-220F-4L)	1.Vin 2.Vout 3.GND 4.Vdis

Ordering Information

Part No	Package	Packing	Finish	Halogen	Packing Unit	Remark
ISP278R05	TO-220F-4L	Tube	Sn	Free	5,000	



Electrical Characteristics

Operating Conditions: $V_I = 7V$, $I_O = 1A$, $V_{CT(High)} = 2.7V$, $T_a = 25^\circ C$, unless otherwise specified





Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Output Voltage	V_O	ISP278R05 $V_I = 6V \sim 12V$	4.88	5.0	5.12	V
Line Regulation	$\Delta V_O(\Delta V_I)$	Note, $I_O = 1.0A$	-	0.5	2.5	%
Load Regulation	$\Delta V_O(\Delta I_L)$	$5mA \leq I_O \leq 2.0A$	-	0.2	2.0	%
Quiescent Current	I_{QC}	$I_O = 0mA$	-	-	10	mA
Ripple Rejection Ratio	RR	$(V_O + 2V) \leq V_I \leq 12V$, $I_O = 50mA$ $f = 120Hz$	45	55	-	dB
Dropout Voltage	V_{DROP}	$I_O = 1.0A$	-	-	0.3	V
		$I_O = 2.0A$	-	-	0.5	V
Control Voltage High	$V_{CT(High)}$	$I_O = 0mA$, Output ON	2.0	-	-	V
Control Voltage Low	$V_{CT(Low)}$	$I_O = 0mA$, Output OFF	-	-	0.8	V
Disable Bias Current H	I_{disH}	$V_{dis} = 2.7V$	-	-	20	μA
Disable Bias Current L	I_{disL}	$V_{dis} = 0.4V$			-0.4	mA

Notes

1. These parameters, although guaranteed, are not 100% tested in production.
2. Junction -to -case thermal resistance test environments.
 - Pneumatic heat sink fixture.
 - Clamping pressure 60psi through 12mm diameter cylinder.
 - Thermal grease applied between PKG and heat sink fixture
3. Connect V_{CT} to V_{IN} when not using V_{CT} pin.



Electrical Characteristics Curves






Package Dimension

TO-220F-4L

Unit : mm





Revision History

No	Date	Contents
1	2015-01-30	Initial Brief Datasheet Release
2	2015-06-22	Added Ttsd ability (150°C)



<http://www.apsemi.com>

IMPORTANT NOTICE

AP Semiconductor co, Ltd reserves the right to make changes without further notice to any products or specifications herein. AP Semiconductor co, Ltd does not assume any responsibility for use of any its products for any particular purpose, nor does AP Semiconductor co, Ltd assume any liability arising out of the application or use of any its products or circuits. AP Semiconductor co, Ltd does not convey any license under its patent rights or other rights nor the rights of others.

AP Semiconductor Co., Ltd

Contact. **Tel** 82.70.4693.2299 **FAX** 82.70.4000.4009

E-mail: sales@apsemi.com

© 2015 AP semiconductor Co., Ltd. – Printed in KOREA – All Rights Reserved.