

Schottky Barrier Rectifier Reverse Voltage 40 to 200 Volts Forward Current 10 Amperes


Features

- Metal silicon junction majority carrier conduction
- Guard ring for overvoltage protection
- Low power loss, high efficiency
- High current capability, low forward voltage drop
- High surge capability
- High temperature soldering guaranteed:
260°C/10 seconds at terminals
- Plastic package has Underwriters Laboratory
Flammability Classification 94V-0
- For use in low voltage, high frequency inverters,
free-wheeling, and polarity protection application

Technical Data

Case : JEDEC ITO-220 molded plastic body

Terminals : Plated axial leads, solderable
per MIL-STD-750, method 2026



Maximum Ratings Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Parameter		Symbol	MBR 1040	MBR 1045	MBR 1060	MBR 1080	MBR 10100	MBR 10120	MBR 10150	MBR 10200	Unit
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	40	50	60	80	100	120	150	200	V
Maximum RMS voltage		V _{RMS}	28	31.5	42	56	70	84	105	140	V
Maximum DC Blocking Voltage		V _{DC}	40	45	60	80	100	120	150	200	V
Maximum Average Forward Rectified Current 0.375" (9.5mm) lead length		I _{F(AV)}	10.0								A
Peak forward surge current, 8.3mS single half sine-wave superimposed on rated load		I _{FSM}	150								A
Maximum instantaneous forward voltage at 1/2I _{F(AV)}		V _F	0.55		0.75		0.85		0.90	0.95	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	T _a = 25°C	I _R	0.5			0.1					mA
	T _a = 100°C		50			10					
Typical Thermal Resistance ⁽²⁾		R _{θJC}	2								°C/W
Operating and Storage Temperature Range		T _J , T _{STG}	-65 to +150								°C





Note

- (1) Single phase, half wave, 60HZ, resistive or inductive load. For capacitive load, derate current by 20%.
- (2) PCB mounted with 0.2X0.2"(5.0X5.0 mm) copper pad areas.



Characteristics Curves


($T_A = 25^\circ\text{C}$ unless otherwise specified)





Package Dimensions

Unit : mm



REV. 00



Revision History

No	Date	Contents
0	2021-06-08	Initial Brief Datasheet Release

<http://www.apsemi.com>

IMPORTANT NOTICE

AP Semiconductor co, Ltd reserves the right to make changes without further notice to any products or specifications herein. AP Semiconductor co, Ltd does not assume any responsibility for use of any its products for any particular purpose, nor does AP Semiconductor co, Ltd assume any liability arising out of the application or use of any its products or circuits. AP Semiconductor co, Ltd does not convey any license under its patent rights or other rights nor the rights of others.

AP Semiconductor Co., Ltd

Contact. **Tel** 82.70.4693.2299 **FAX** 82.70.4000.4009

E-mail: sales@apsemi.com

© 2015 AP semiconductor Co., Ltd. –Printed in KOREA –All Rights Reserved.